

機種選定表

断熱厚(mm)		100		75		50			
庫内温度(°C)		-25°C	-20°C	-15°C	-10°C	-5°C	0°C	+5°C	+10°C
車両クラス (ton)	容積 (m <sup>3</sup> )								
1	3.5								
	4								
	4.5			DS11LN-S1MN1		D11MN-S1SN1		D21CN-1EU1	
	5			DS12LN-S1MN1		D12MN-S1SN1		D22CN-1EU1	
	5.5								
6									
6.5									
7									
7.5									
8									
8.5									
9			S13LN-S2MN-11S						
9.5			S13LN-S2MN-21S						
10			DS22LN-P21						
10.5						S13MN-S2SN-11			
11						S13MN-S2SN-21			
11.5									
12									
12.5									
13									
13.5									
14									
14.5									
15			S19LN-S3MN-21S						
16			DS32LN-P32						
17						S20MN-S2MN-21S			
18									
19									
20									
21									
22									
23			S28-LN-S4LN-22S						
24			DS42LN-EP32			S25MN-S3MN-21S			
25			P28LN-P4-22S						
26			DS52LN-ES5LN2						
27									
28									
29									
30									
31									
32									
33									
34					DS42LN-EP42				
35									
36									
37									
38									
39									
40					DS72LN-EP72				
41									
42									
43									
44									
45									
46					DS82LN-EP82				
47									
48									
49									
50									

※2コンプ2エバ(3コンプ)直結式冷凍機をご使用ください。