

機種選定表
メインエンジン型

TZシリーズ(低温)

断熱厚(mm)		100		75		50				
庫内温度(°C)		-25°C	-20°C	-15°C	-10°C	-5°C	0°C	+5°C	+10°C	+15°C
車種クラス(ton)	容積(m ³)	適用冷凍機型式								
3	3									
3.5	3.5									
4	4									
4.5	4.5									
5	5									
5.5	5.5									
6	6									
6.5	6.5									
7	7									
7.5	7.5									
8	8									
8.5	8.5									
9	9									
9.5	9.5									
10	10									
10.5	10.5									
11	11									
11.5	11.5									
12	12									
12.5	12.5									
13	13									
13.5	13.5									
14	14									
14.5	14.5									
15	15									
16	16									
17	17									
18	18									
19	19									
20	20									
21	21									
22	22									
23	23									
24	24									
25	25									
26	26									
27	27									
28	28									
29	29									
30	30									
31	31									
32	32									
33	33									
34	34									
35	35									
36	36									
37	37									
38	38									
39	39									
40	40									
41	41									
42	42									
43	43									
44	44									

Zシリーズ(低温)

断熱厚(mm)		100		75		50				
庫内温度(°C)		-25°C	-20°C	-15°C	-10°C	-5°C	0°C	+5°C	+10°C	+15°C
車種クラス(ton)	容積(m ³)	適用冷凍機型式								
3	3									
3.5	3.5									
4	4									
4.5	4.5									
5	5									
5.5	5.5									
6	6									
6.5	6.5									
7	7									
7.5	7.5									
8	8									
8.5	8.5									
9	9									
9.5	9.5									
10	10									
10.5	10.5									
11	11									
11.5	11.5									
12	12									
12.5	12.5									
13	13									
13.5	13.5									
14	14									
14.5	14.5									
15	15									
16	16									
17	17									
18	18									
19	19									
20	20									
21	21									
22	22									
23	23									
24	24									
25	25									
26	26									
27	27									
28	28									
29	29									
30	30									
31	31									
32	32									
33	33									
34	34									
35	35									
36	36									
37	37									
38	38									
39	39									
40	40									
41	41									
42	42									
43	43									
44	44									

Zシリーズ(中温)

断熱厚(mm)		50					
庫内温度(°C)		0°C	+5°C	+10°C	+15°C	+20°C	+25°C
車種クラス(ton)	容積(m ³)	適用冷凍機型式					
3	3						
3.5	3.5						
4	4						
4.5	4.5						
5	5						
5.5	5.5						
6	6						
6.5	6.5						
7	7						
7.5	7.5						
8	8						
8.5	8.5						
9	9						
9.5	9.5						
10	10						
10.5	10.5						
11	11						
11.5	11.5						
12	12						
12.5	12.5						
13	13						
13.5	13.5						
14	14						
14.5	14.5						
15	15						
16	16						
17	17						
18	18						
19	19						
20	20						
21	21						
22	22						
23	23						
24	24						
25	25						
26	26						
27	27						
28	28						
29	29						
30	30						
31	31						
32	32						
33	33						
34	34						
35	35						
36	36						
37	37						
38	38						
39	39						
40	40						
41	41						
42	42						
43	43						
44	44						

機種選定表

サブエンジン型

断熱厚(mm)		100		75		50			
庫内温度(°C)		-25°C	-20°C	-15°C	-10°C	-5°C	0°C	+5°C	+10°C
車両クラス(ton)	容積(m³)								
	19								
	20								
	21								
	23								
	25								
	27								
	29	UT-1200SR/T-1200R/T1200R SPECTRUM							
	31								
	32								
	34								
	37								
	39								
	41								
	44								
	47								
	50								
	55								
	57								
	60								
	63	SB-230/SPECTRUM SB/SLX-400/SLX-SRECTRUM							
	65								
	68								
	70								

